

X-band High Power Amplifier


GaAs Monolithic Microwave IC

Description

The CHA7215 is a monolithic three-stage GaAs high power amplifier designed for X band applications.


The HPA provides typically 9W output power associated to 35% power added efficiency at 4dBc and a high robustness on mismatch load.

This device is manufactured using 0.25 μm Power pHEMT process, including, via holes through the substrate and air bridges.



Main Features

- 0.25 μm Power pHEMT Technology
- Frequency band: 8.5 – 11.5GHz
- Output power: 39.5dBm at saturation
- High linear gain: 28dB
- Power added efficiency: 34% @4dBc
- Quiescent bias point: $V_d=8\text{V}$, $I_d=2.3\text{A}$
- Chip size: 5 x 3.31 x 0.07mm



Main Characteristics

$V_d=8\text{V}$, I_d (Quiescent) = 2.3A, Drain Pulse width = 25 μs , Duty cycle = 10%

Symbol	Parameter	Min	Typ	Max	Unit
Top	Operating temperature range	-40		+80	°C
Fop	Operating frequency range	8.5		11.5	GHz
PAE_4dBc	Power added efficiency @4dBc @ 20°C		34		%
Psat	Saturated output power @ 20°C		39.5		dBm
G	Small signal gain @ 20°C	25	28	31	dB

ESD Protections: Electrostatic discharge sensitive device. Observe handling precautions!

Electrical Characteristics on test fixture

Tamb = 20°C, Vd=8V, Id (Quiescent) = 2.3A, Drain Pulse width = 25µs, Duty cycle = 10%

Symbol	Parameter	Min	Typ	Max	Unit
Fop	Operating frequency	8.5		11.5	GHz
G	Small signal gain	25	28	31	dB
G_T	Small signal gain variation versus temperature		-0.05		dB/°C
RLin	Input Return Loss		10		dB
RLout	Output Return Loss		12		dB
Psat	Saturated output power		39.5		dBm
Psat_T	Saturated output power variation versus temperature		-0.01		dB/°C
PAE_4dBc	Power added efficiency @4dBc		34		%
Id_4dBc	Supply drain current @ 4dBc		3.3	4.4	A
Vd1, Vd2, Vd3	Drain supply voltage (2)		8		V
Id	Supply quiescent current (1)		2.3		A
Vg1, Vg2, Vg3	Gate supply voltage		-2.2		V

(1) Parameter can be adjusted by tuning of Vg.

(2) 0.5V variation on Vd leads to around 0.4dB variation of the output power (impact on robustness see Maximum ratings)

Absolute Maximum Ratings (1)

Tamb = 20°C

Symbol	Parameter	Values	Unit
Cmp	Compression level (2)	6	dBc
Vd	Supply voltage with RF input power	9	V
Vd	Supply voltage without RF input power	10	V
Id	Supply quiescent current	3	A
Id_sat	Supply current in saturation	4.8	A
Vg	Supply voltage	-1.1	V
Tj	Maximum junction temperature	175	°C
Tstg	Storage temperature range	-55 to +125	°C
Top	Operating temperature range	-40 to +80	°C


(1) Operation of this device above anyone of these parameters may cause permanent damage.

(2) For higher compression the level limit can be increased by decreasing the voltage Vd using the rate 0.5 V / dBc


Typical measured characteristics

Measurements on Jig:


Vd=8V, Id (Quiescent) = 2.3A, Drain Pulse width = 25µs, Duty cycle = 10%




Linear gain versus frequency and temperature




Linear Gain and Output Power @ Freq=10GHz versus input power and temperature



Output Power @Pin=17dBm versus frequency and temperature




Id @Pin=17dBm versus frequency and temperature



PAE @Pin=17dBm versus frequency and temperature

Chip Mechanical Data and Pin references



UNITS : μm
Tol : $\pm 35\mu\text{m}$


Chip thickness = $70\mu\text{m} \pm 10\mu\text{m}$
 RF pads (1, 15) = $(122 \times 200)\mu\text{m}^2$
 DC pads (2 to 12, 14, 16, 18 to 28) = $(100 \times 100)\mu\text{m}^2$
 DC pads (13, 17) = $(186 \times 100)\mu\text{m}^2$

Pin number	Pin name	Description
1, 15	IN / OUT	Input / Output RF
3, 8, 12, 18	GiR	Gate supply voltage
4, 6, 10, 14, 16, 20, 24, 26	M	Ground (Not connected)
5, 9, 13, 17, 21, 25	Di	Drain supply voltage
2, 7, 11, 19, 22, 23, 27, 28	Gi / GiR	Not connected

Bonding recommendations

Port	Connection	External capacitor
IN	Inductance (L _{bonding}) = 0.35nH 2 gold wires with diameter of 25 μm (600μm max)	
OUT	Inductance (L _{bonding}) = 0.35nH 2 gold wires with diameter of 25 μm (600μm max)	
Vg	Inductance ≤ 1nH	C1 ~ 100pF C2 ~ 10nF
Vd	Inductance ≤ 1nH	C1 ~ 100pF

Assembly recommendations in test fixture



Recommended ESD management

Refer to the application note AN0020 available at <http://www.ums-gaas.com> for ESD sensitivity and handling recommendations for the UMS products.

Ordering Information

Chip form : CHA7215-99F/00

Information furnished is believed to be accurate and reliable. However **United Monolithic Semiconductors S.A.S.** assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of **United Monolithic Semiconductors S.A.S.** Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. **United Monolithic Semiconductors S.A.S.** products are not authorised for use as critical components in life support devices or systems without express written approval from **United Monolithic Semiconductors S.A.S.**