



Product Overview

The CMD317C4 is a wideband GaAs MMIC driver amplifier housed in a leadless 4x4 mm surface mount package. The CMD317C4 is ideally suited for military, space and communications systems where small size and high linearity are needed. At 12 GHz the device delivers 16 dB of gain with a corresponding output 1 dB compression point of +23 dBm and an output IP3 of 35 dBm. The CMD317C4 is a 50 ohm matched design which eliminates the need for RF port matching and includes an on chip bias choke.



Functional Block Diagram



Key Features

- Wide Bandwidth
- High Linearity
- Single Positive Supply Voltage
- On Chip Bias Choke
- Pb-Free RoHs Compliant 4x4 mm SMT Package

Ordering Information

| Part No. | Description |
|--------------|--------------------|
| CMD317C4 | 100 pcs on 7" reel |
| CMD317C4-EVB | Evaluation Board |

Electrical Performance ($V_{dd} = 8.0 \text{ V}$, $T_A = 25^\circ \text{C}$, $F = 12 \text{ GHz}$)

| Parameter | Min | Typ | Max | Units |
|--------------------|-----|--------|-----|-------|
| Frequency Range | | 1 - 24 | | GHz |
| Gain | | 16 | | dB |
| Input Return Loss | | 18 | | dB |
| Output Return Loss | | 16 | | dB |
| Output P1dB | | 23 | | dBm |
| Output IP3 | | 35 | | dBm |
| Supply Current | | 225 | | mA |

Absolute Maximum Ratings

| Parameter | Rating |
|-------------------------------|---------------|
| Drain Voltage, V_{dd} | 9 V |
| RF Input Power | +20 dBm |
| Channel Temperature, T_{ch} | 150° C |
| Power Dissipation, P_{diss} | 2.62 W |
| Thermal Resistance, Q_{JC} | 24.8° C/W |
| Operating Temperature | -55 to 85° C |
| Storage Temperature | -55 to 150° C |

Exceeding any one or combination of the maximum ratings may cause permanent damage to the device.

Recommended Operating Conditions

| Parameter | Min | Typ | Max | Units |
|-----------|-----|-----|-----|-------|
| V_{dd} | 5.0 | 8.0 | 8.5 | V |
| I_{dd} | | 225 | | mA |

Electrical performance is measured at specific test conditions. Electrical specifications are not guaranteed over all recommended operating conditions.

Drain Current vs. Drain Voltage


| V_{dd} (V) | I_{dd} (mA) |
|--------------|---------------|
| 5.0 | 130 |
| 8.0 | 225 |

Electrical Specifications ($V_{dd} = 8.0$ V, $T_A = 25^\circ$ C)


| Parameter | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | Units |
|--------------------------------------|--------|-------|-----|---------|-------|-----|---------|-------|-----|-------|
| Frequency Range | 1 - 10 | | | 10 - 20 | | | 20 - 24 | | | GHz |
| Gain | 10.5 | 15 | | 12.5 | 17 | | 9.5 | 15 | | dB |
| Noise Figure | | 4 | | | 3.5 | | | 6.5 | | dB |
| Input Return Loss | | 15 | | | 15 | | | 10 | | dB |
| Output Return Loss | | 13 | | | 10 | | | 12 | | dB |
| Output P1dB | 19.5 | 23 | | 18 | 22 | | 15 | 19 | | dBm |
| Output IP3 | | 36 | | | 34 | | | 27 | | dBm |
| Supply Current | 170 | 225 | 280 | 170 | 225 | 280 | 170 | 225 | 280 | mA |
| Gain Temperature Coefficient | | 0.012 | | | 0.014 | | | 0.023 | | dB/°C |
| Noise Figure Temperature Coefficient | | 0.009 | | | 0.012 | | | 0.016 | | dB/°C |

Typical Performance

Broadband Performance, $V_{dd} = 8.0\text{ V}$, $T_A = 25^\circ\text{C}$




Narrow-band Performance, $V_{dd} = 8.0\text{ V}$, $T_A = 25^\circ\text{C}$




Typical Performance

Gain vs. Temperature, $V_{dd} = 8.0\text{ V}$




Gain vs. V_{dd} , $T_A = 25^\circ\text{ C}$




Typical Performance

Noise Figure vs. Temperature, $V_{dd} = 8.0\text{ V}$




Noise Figure vs. V_{dd} , $T_A = 25^\circ\text{ C}$




Typical Performance

P1dB vs. Temperature, $V_{dd} = 8.0\text{ V}$




P1dB vs. V_{dd} , $T_A = 25^\circ\text{C}$




Typical Performance

Psat vs. Temperature, $V_{dd} = 8.0\text{ V}$




Psat vs. V_{dd} , $T_A = 25^\circ\text{ C}$




Typical Performance

Output IP3 vs. Temperature, $V_{dd} = 8.0\text{ V}$




Output IP3 vs. V_{dd} , $T_A = 25^\circ\text{C}$




Typical Performance

Output IP2 vs. Temperature, $V_{dd} = 8.0\text{ V}$




Output IP2 vs. V_{dd} , $T_A = 25^\circ\text{ C}$



Pin Description

Pin Diagram




Functional Description

| Pad | Function | Description | Schematic |
|-----------------------------------|-----------------|--|-----------|
| 1, 2, 6 - 9, 11 - 14, 18 - 22, 24 | N/C | No connection required These pins may be connected to RF / DC ground | |
| 3, 5, 15, 17 and die paddle | Ground | Connect to RF / DC ground | |
| 4 | RF in | 50 ohm matched input External DC block required | |
| 23 | V _{dd} | Power supply voltage Decoupling and bypass caps required | |
| 16 | RF out | 50 ohm matched input External DC block required | |
| 10 | ACG | Low frequency termination Attach bypass capacitor per application circuit | |

Applications Information

Application Circuit



Biasing and Operation

The CMD317C4 is biased with a single positive drain supply. Performance is optimized when the drain voltage is set to +8.0 V.

Turn ON procedure:

1. Apply drain voltage V_{dd} and set to +8 V

Turn OFF procedure:

1. Turn off drain voltage V_{dd}


RF power can be applied at any time.

GaAs MMIC devices are susceptible to damage from Electrostatic Discharge. Proper precautions should be observed during handling, assembly and test.

Applications Information

Evaluation Board

The circuit board shown has been developed for optimized assembly at Qorvo. A sufficient number of via holes should be used to connect the top and bottom ground planes. As surface mount processes vary, careful process development is recommended.



Bill of Material

| Designator | Value | Description |
|------------|--------------|---------------------------|
| J1, J2 | | SMA End Launch Connector |
| P1 | | 6 Pin Header |
| C1, C4 | 0.33 μ F | Capacitor, Tantalum |
| C5 | 1000 pF | Capacitor, 0603 |
| C9 | 100 pF | Capacitor, 0402 |
| U1 | | CMD317C4 Driver Amplifier |
| PCB | | 100541 Evaluation PCB |

RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Lead Free
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- SVHC Free
- PFOS Free
- Halogen Free



Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Web: www.qorvo.com

Tel: 1-844-890-8163

Email: customer.support@qorvo.com

Important Notice

The information contained in this Data Sheet and any associated documents (“Data Sheet Information”) is believed to be reliable; however, Qorvo makes no warranties regarding the Data Sheet Information and assumes no responsibility or liability whatsoever for the use of said information. All Data Sheet Information is subject to change without notice. Customers should obtain and verify the latest relevant Data Sheet Information before placing orders for Qorvo® products. Data Sheet Information or the use thereof does not grant, explicitly, implicitly or otherwise any rights or licenses to any third party with respect to patents or any other intellectual property whether with regard to such Data Sheet Information itself or anything described by such information.

DATA SHEET INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Without limiting the generality of the foregoing, Qorvo® products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death. Applications described in the Data Sheet Information are for illustrative purposes only. Customers are responsible for validating that a particular product described in the Data Sheet Information is suitable for use in a particular application.

© 2020 Qorvo US, Inc. All rights reserved. This document is subject to copyright laws in various jurisdictions worldwide and may not be reproduced or distributed, in whole or in part, without the express written consent of Qorvo US, Inc. | QORVO® is a registered trademark of Qorvo US, Inc.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Qorvo:](#)

[CMD317C4](#)